



Terminal housing for Verifone UX700 and Logos Valina. Options include Controller, Printer, Column, Wall bracket, etc.

| | | | | | |
|-----------------|---|--|----------------------|---|---|
| Material | Exterior: Stainless steel (1,5 mm, 316) Inside: Brackets/fittings etc. in aluminum | | Power | 230 VAC 50 Hz 1,3 A | |
| Size | Head | 230 x 220 x 410 mm WxDxH | Environmental | For outdoor use Operating Temperature: -30° C to +70° C Storage Temperature: -30° C to +80° C Relative Humidity: 5% to 90%, Non-condensing | |
| | Column | H1 830 mm H2 980 mm H3 1130 mm | | IP65 IK08 | |
| | Wall bracket | 230 x 30 x 455 mm WxDxH | | | |
| Weight | Head | 11,6 kg | Color | Standard color: RAL 9016 Traffic White, gloss 80 Other RAL colors are available | |
| | Column | H1 16,3 kg H2 17,7 kg H3 19,1 kg | | | |
| | Wall bracket | 2,1 kg | | | |
| Options | Printer 4G/5G modem I/O Boards & UPI Boards iButton Reader Controller for Refueling & Cars Wash Forecourt Controller ANPR Cameras | | Use cases | EV Charging Ticketing Ferries Car Wash | Parking Toll-roads Refueling Advanced Payments |

All features and specifications are subject to change without notice, and do not constitute a warranty of any kind, including, but not limited to, warranties of merchantability or fitness for a particular purpose. Product display image for representation purposes only. Actual product display may vary. Reproduction or posting of this document without prior Logos approval is prohibited.